



OLA DeoMAX DM8 SAE 15W-40

High performance diesel engine oil

Specification:

- API CG-4/CF-4/CF/SJ
- ACEA E3 /A3/B3
- MB 228.0 / 228.1
- MAN 271

Features and benefits:

OLA DeoMAX DM8 is a high technology oil and particularly efficient in modern diesel engines and older conception engine. It provides the potential advantage below:

- Control of deposits and mud build-up.
- Excellent cleanliness properties and extend engine life.
- Reduce oil consumption and engine wear.

Description:

OLA DeoMAX DM8 is high performance oil for diesel engine working in severe conditions. DeoMAX DM8 is recommended for variety of engines: on-highway light and heavy trucking and off highway engines: construction, mining, quarrying, and agriculture.

Applications:

- Natural aspirated and turbo-charged diesel engines.
- On-highway light and heavy-duty.
- Off highway industries including: construction, mining, quarrying, and Agriculture.

Typical properties:

	Test Method	DeoMAX DM8 SAE 15W-40
Grade SAE		15W-40
Viscosity @ 40°C-cSt	ASTM D 445	110.5
Viscosity @ 100°C-cSt	ASTM D 445	14.2
Viscosity Index	ASTM D 2270	136
TBN - mg KOH/g	ASTM D 2896	8.6
Pour point °C	ASTM D 97	-27
Flash Point °C	ASTM D 92	228
Density @ 15°C - kg/l	ASTM D 4052	0.88

The characteristic values appeared on the top in the table are typical values given only as an indication

Health and safety:

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of this product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.