



OLA MotoPower HP 20W-50

High performance 4 stroke engine oil

Specification:

- API SG
- JASO MA/MA-2

Features and benefits:

- Delivers superior engine wear protection and high film strength for high revving motorcycle engines.
- Specialized additives help prevent ring sticking and build-up of harmful deposits.

Description:

OLA MotoPower HP 20W-50 is a mineral based 4-stroke motorcycle oil specially formulated to provide outstanding protection under severe high torque, high stress conditions. Under these conditions, motorcycle engines operate at extremely high temperatures causing viscosity and thermal breakdown of motor oil. MotoPower HP 20W-50 provides maximum protection against viscosity and thermal breakdown.

Applications:

OLA MotoPower HP 20W-50 is specially designed for use in the 4-stroke motorcycle engines, which require JASO MA/MA-2 performance.

Typical properties:

	Test Method	MotoPower HP 20W-50
Viscosity @ 100°C-cSt	ASTM D 445	18,4
Viscosity Index	ASTM D 2270	95
TBN mgKOH/g	ASTM D 2896	7,2
Pour Point °C	ASTM D 97	-12
Density @ 20°C - kg/l	ASTM D 4052	0,89

The characteristic values appeared on the top in the table are typical values given only as an indication

Health and safety:

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of this product is available for a simple request from your sales contact once or via internet. In case of used oil elimination, please respect the regulation and protect the environment.