



OLA MotoPower SAE 40

4 Stroke motorcycle engine oil

Specification:

API SF

Description:

OLA MotoPower SAE 40 is a monograde 4 stroke motorcycle oil formulated to provide protection to vital parts of the engine in severe riding conditions.

Features and benefits:

Formulated from quality mineral base and selected additives MotoPower SAE 40 provides superior engine protection under a variety of operating conditions. It protects the engine against deposit build-up, wear and corrosion, allowing it to remain in perfect operating condition.

Applications:

OLA MotoPower SAE 40 is recommended to use in the 4 stroke motorcycle engines such as underbones, mopeds and scooters equipped with small hot-running engines.

Typical properties:

Characteristics	Test Method	MotoPower SAE 40
SAE Grade		40
Viscosity @ 40°C - cSt	ASTM D 445	141
Viscosity @ 100°C - cSt	ASTM D 445	14.2
Viscosity Index	ASTM D 2270	98
TBN - mg KOH/g	ASTM D 2896	5.7
Pour Point °C	ASTM D 97	- 6
Flash Point °C	ASTM D 92	224
Density @ 20°C - kg/l	ASTM D 4052	0,89

The characteristic values appeared on the top in the table are typical values given only as an indication

Health and safety:

This product is not expected to cause any risk if used as per our recommendation and intended application. A safety data sheet is available on a simple request from your sales contact or a download from OLA Energy website. In case of used oil disposal, please respect the local regulation and protect the environment.