



OLA Accel ULTRA S 10W-40

High performance semi-synthetic engine oil

Specification:

- ACEA A3/ B4-2016
- API SN/CF
- MB 229.3
- VW 502 00/505 00
- PSA B 71 2300
- Renault RN 0700/0710

Description:

OLA Accel Ultra S 10W-40 is semi-synthetic engine oil for passenger and light duty diesel cars formulated with modern technology components and synthetic base oils offering excellent qualities.

Applications:

- OLA Accel Ultra S 10W-40 is specifically recommended for use in all types of vehicles, especially modern gasoline or diesel engines (also multi-valve fuel injection engines), turbochargers and other high performance engines.
- OLA Accel Ultra S 10W-40 is an excellent choice who is seeking outstanding lubricant. It is intended for all automobiles, light trucks and vans.

Features and benefits:

OLA Accel ULTRA S 10W-40 is specially formulated with the highest quality synthetic & mineral base oils and leading additive technology to provide the highest protection in a wide range of operating conditions.

Key features and benefits include:

- Excellent thermal and oxidation stability to reduce engine deposits and sludge build up to keep engines running reliably.

- Effective detergency/dispersancy : cleaner engines and long engine life.
- Enhanced frictional properties to help save fuel.
- Excellent low temperature capabilities for reliable cold weather starting allowing fast engine protection.
- High temperature fortified formulation provides reserve protection for the toughest driving conditions.

Typical properties:

Characteristics	Methods	Units	Values
Density at 15°C	ASTM D 4052	-	0,873
Kinematic viscosity @ 100°C	ASTM D 445	cSt	13.8
Kinematic viscosity @ 40°C	ASTM D 445	cSt	92.3
Viscosity index	ASTM D 2270	-	152
TBN	ASTM D 2896	mg KOH/g	10,1
Flash point	ASTM D 92	°C	> 220
Pour point	ASTM D 97	°C	<-30
Sulfated ash	ASTM D 874	wt%	1.3

The characteristic values appeared on the top in the table are typical values given only as an indication

Health and safety:

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of this product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.