



OLA DeoMAX DM12 SAE 15W-40

Extra high performance multigrade diesel engine oil

Specification:

- API CI-4 / CG-4 / CF-4 / CF/SL/SJ
- ACEA E7/ A3 / B4/
- MB 228.3(p)/229.1; MAN3275; Volvo VDS-3; MTU2.0; MACK EO-M PLUS
- Cummins CES 20076 / CES 20077 / CES 20078
- Caterpillar ECF-1a
- Renault RLD-2 ; Detroit diesel 93K215
- Deutz DQL III-05 ; Global DHD-1

Recommended for the following engines:

- JBC
- KOMATSU
- LIEBHERR
- PERKINS
- CASE NEW-HOLLAND

Description:

OLA DeoMAX DM12 is premium high performance diesel engine oil for variety of classic and modern engines, high output engines, including those with exhaust gas (EGR) working under severe conditions. DeoMAX DM12 helps extend engines life in the most demanding on and off road and meets or exceeds the specifications of virtually all major engine manufacturers.

Applications:

- Natural aspirated and turbo-charged diesel engines.
- On-highway light and heavy-duty.
- Off highway industries including :construction, mining, quarrying, and agriculture ...

Features and benefits:

OLA DeoMAX DM12 is particularly efficient in modern diesel and gasoline engines and older conception engine. It provides the potential advantage below:

- Outstanding pump ability and circulation to restrict wear when start.
- Excellent viscosity/temperature control that reduces engine wear and cylinders polishing.

- Exceptional detergency /dispersency to better control mud and deposits build-up.
- Excellent shear stability to reduce oil consumption.



OLA DeoMAX DM12 SAE 15W-40

Typical properties:

	Test Method	DeoMAX DM12
Grade SAE		15W-40
Viscosity @ 40°C-cSt	ASTM D 445	99
Viscosity @ 100°C-cSt	ASTM D 445	13.3
Viscosity Index	ASTM D 2270	133
TBN - mg KOH/g	ASTM D 2896	10.3
Pour point °C	ASTM D 97	-33
Flash Point °C	ASTM D 92	226
Density @ 15°C - kg/l	ASTM D 4052	0,879

The characteristic values appeared on the top in the table are typical values given only as an indication

Health and safety:

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of this product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.