



# OLA Accel XL8 20W-50

## High performance multigrade passenger vehicle engine oil

### Specification:

API SG/CF

### Description:

OLA Accel XL8 is high performance engine oil for all vehicles, formulated with a propriety mixture of refine base oils and a superior additive system that provides an excellent protection and engine cleanness. Accel XL8 reduces engine's wear and protects it from the rust and deposit build-up (soot, varnish, lacquer....).

### Features and benefits:

- Optimal protection engine's wear.
- Facilitates start when cold.
- Guarantees an excellent engine protection in high temperature.
- Reduces oil consumption.

### Applications:

OLA Accel XL8 can be used in a variety of gasoline and diesel engines requiring a level performance API SG/CF.

### Typical properties:

	Test Method	Accel XL 8
<b>Grade SAE</b>		20W-50
Viscosity @ 40°C-cSt	ASTM D 445	149
Viscosity @ 100°C-cSt	ASTM D 445	17
Viscosity Index	ASTM D 2270	123
TBN - mg KOH/g	ASTM D 2896	8.7
Pour point °C	ASTM D 97	-27
Flash Point °C	ASTM D 92	230
Density @ 15°C - kg/l	ASTM D 4052	0,896

The characteristic values appeared on the top in the table are typical values given only as an indication

### Health and safety:

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of this product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.