



OLA Accel XLD10 SAE 15W-40

High performance multigrade engine oil

Specification:

API CF-4/SJ

Description:

OLA Accel XLD 10 is premium multigrade oil that exceeds the latest standards required in all modern engines. It is formulated from a high quality of mineral base oil and an outstanding additive system.

Features and benefits:

OLA Accel XLD 10 protects the engine and maintains its cleanliness, avoids sludge and varnish build-up, and fights wear and corrosion under all driving conditions.

Applications:

OLA Accel XLD 10 is recommended for all modern engines requiring a level performance API CF-4/SJ.

Typical properties:

	Test Method	Accel XLD 10
Grade SAE		15W-40
Viscosity @ 40°C-cSt	ASTM D 445	104.5
Viscosity @ 100°C-cSt	ASTM D 445	14.0
Viscosity Index	ASTM D 2270	135
TBN - mg KOH/g	ASTM D 2896	7
Pour point °C	ASTM D 97	-33
Flash Point °C	ASTM D 92	228
Density @ 20°C - kg/l	ASTM D 4052	0.881

The characteristic values appeared on the top in the table are typical values given only as an indication

Health and safety:

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of this product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.