



OLA Agrol SUPER 15W-40

Super tractor oil universal

Specification:

- API CG-4/SF
- API GL-4
- ACEA E3
- ZF TE ML 06A, B, C and 07B
- Ford M2C 159B/C - Ford M2C 134D
- New Holland 82009201/3
- CASE New Holland MAT 3525 and 3526
- John Deere J27/J20C
- Massey Fergusson CMS M 1135, 1139, 1143, 1144 & 1145

Description:

OLA Agrol Super 15W-40 is high performance STOU working in severe conditions recommended for use in the following systems in farm tractors and implements: crankcase of diesel and four stroke gasoline engines, hydraulics, transmissions, wet brakes, power take offs, hydrostatics and power steering.

Applications:

- Mixed diesel and gasoline-powered farm vehicles and equipment.
- Farm equipment transmissions and power systems requiring multifunctional fluid.

Features and benefits:

Agricultural enterprises employ a wide variety of equipment requiring multi-functional lubrication performance. The engineering in OLA Agrol Super 15W-40 meets the diverse lubrication requirements of this equipment which reduces the number of lubricants required and the possibility of misapplication. The key benefits include:

- Good thermal and oxidation stability.
- Reduced sludge build-up and high temperature deposits.

- Good rust and corrosion protection.
- Reduced wear and longer equipment life especially in hydraulic components.
- Effective detergency/dispersancy cleaner engines and longer engine life.
- High temperature viscosity retention and volatility control.
- Reduced engine scuffing, bore polishing and oil consumption.
- TBN reserves Improved deposit control.

Typical properties:

	Test Method	Agrol Super 15W-40
Grade SAE		15W-40
Viscosity @ 40°C - cSt	ASTM D 445	110.5
Viscosity @ 100°C - cSt	ASTM D 445	14.3
Viscosity Index	ASTM D 2270	136
Pour Point °C	ASTM D 97	-33
Flash point °C	ASTM D 92	228
TBN	ASTM D 2896	10
Sulfated Ash	ASTM D 874	1.2
Density @ 20°C - kg/l	ASTM D 4052	0.88

The characteristic values appeared on the top in the table are typical values given only as an indication



OLA Agrol SUPER 15W-40

Health and safety:

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of this product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.