



OLA DeoMAX DM5 SAE 30,40,50

High performance monograde engine oil

Specification:

API CF

Description:

OLA DeoMAX DM5 SAE 30,40,50 monograde oils formulated with a mixture of high performance base oils and balanced additive system. These products are conceived especially for turbo-charged diesel engines and natural aspirated working under severe operating conditions such as on and off - highways segments.

Features and benefits:

OLA DeoMAX DM5 SAE 30, 40, 50 provide the potential advantages below:

- Protection against engine's wear.
- Extend deposits control.
- Advanced detergency/dispersancy and extend engine life.

Applications:

- Naturally aspirated and turbo-charged diesel powered equipment.
- Light and heavy-duty trucks and diesel powered equipment in the construction, mining, quarrying, and agriculture industries.

Typical properties:

	Methods	DM 5 SAE 30	DM 5 SAE 40	DM 5 SAE 50
Grade SAE		30	40	50
Viscosity @ 40°C-cSt	ASTM D 445	90	138	199
Viscosity @ 100°C-cSt	ASTM D 445	10.8	14.0	17.8
Viscosity Index	ASTM D 2270	104	98	97
TBN - mg KOH/g	ASTM D 2896	7.3	7.3	7.3
Pour point °C	ASTM D 97	-12	-12	-12
Flash Point °C	ASTM D 92	246	270	278
Density @ 15°C - kg/l	ASTM D 4052	0.879	0.882	0.886

The characteristic values appeared on the top in the table are typical values given only as an indication

Health and safety:

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of this product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.