



# OLA Process Oil Series

## Paraffinic process oils

### Specification:

API CF

### Description:

Process Oil Series are paraffinic process oil family with a light color and good color stability. It gives improved resiliency, good extrudability, reduced heat build-up, and better low temperature flexibility. It is particularly recommended for use for several manufacturing products such as rubbers.

### Features and benefits:

The advantages to use this kind of products are:

- Light color.
- Good oxidation stability.
- Compatible with elastomers.
- High viscosity index.
- Good solubility propriety

### Applications:

Process Oil Series are typically used in the following applications:

- Tyre liners and tubes
- Weather-stripping
- Vibration dampers and bushings
- Sporting goods
- Plastics
- Additives
- Adhesives, paints, resins and sealing agents
- Leather and textile process

### Typical properties:

	Test Method	Process Oil 30	Process Oil 112	Process Oil 400
Viscosity @ 40°C cSt	ASTM D 445	31	112.9	485.5
Viscosity Index	ASTM D 2270	100	98	95
Pour Point °C	ASTM D 97	-12	-6	-6
Flash Point °C	ASTM D 92	210	266	300
Density @15°C - kg/l	ASTM D 4052	0.86	0.88	0.90

The characteristic values appeared on the top in the table are typical values given only as an indication

### Health and safety:

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of this product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.