



OLA DEOMAX HD 10W

High performance hydraulic oil

Specification:

API CF

Description:

OLA DeoMAX HD 10W is high performance hydraulic oil Formulated from high quality base oils and selected additive system. OLA DeoMAX HD 10W contains an effective balance of ashless dispersant and metallic detergent combined with inhibitors to control corrosion, oxidation, wear and rust. It used in a wide range of hydraulic equipments.

Features and benefits:

OLA DeoMAX HD 10W provides the advantage below:

- Protection against deposits and varnish build-up.
- Offers an excellent wear protection.
- Assures an extend performance in a wide temperature range.

Applications:

- Used in most hydraulic systems.
- Hydraulic systems working in a large temperature rang.
- Combined hydraulic systems with gears and bearings where good anti-wear are required.
- All hydraulic circuit on construction engines equipments, career and agriculture.

Typical properties:

	Test Method	DeoMAX HD 10W
Grade SAE		10W
Viscosity @ 40°C-cSt	ASTM D 445	36.4
Viscosity @ 100°C-cSt	ASTM D 445	6
Viscosity Index	ASTM D 2270	109
TBN - mg KOH/g	ASTM D 2896	6
Pour point °C	ASTM D 97	-18
Flash Point °C	ASTM D 92	224
Density @ 15°C - kg/l	ASTM D 4052	0.88

The characteristic values appeared on the top in the table are typical values given only as an indication

Health and safety:

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of this product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.