



OLA DeoMAX DM7 SAE 15W-40

High performance multigrade diesel engine oil

Specification:

API CF-4/SJ

Description:

OLA DeoMAX DM7 is a high performance oil for diesel engine working in severe conditions. OLA DeoMAX DM7 is recommended for variety of engines: on-highway light and heavy trucking and off highway engines: construction, mining, quarrying, and agriculture.

Features and benefits:

OLA DeoMAX DM7 is a high technology oil and particularly efficient in modern diesel engines and older conception engine. It provides the potential advantage bellow:

- Control of deposits and mud build-up.
- Excellent cleanliness properties and extend engine life.
- Reduce oil consumption and engine wear.

Applications:

- Natural aspirated and turbo-charged diesel engines.
- On-highway light and heavy-duty.
- Off highway industries including: construction, mining, quarrying, and Agriculture.

Typical properties:

	Test Method	DeoMAX DM7 SAE 15W-40
Grade SAE		15W-40
Viscosity @ 40°C-cSt	ASTMD 445	104.5
Viscosity @ 100°C-cSt	ASTMD 445	14.0
Viscosity Index	ASTMD 2270	135
TBN - mg KOH/g	ASTMD 2896	7.3
Pour point °C	ASTMD 97	-33
Flash Point °C	ASTMD 92	228
Density @ 15°C - kg/l	ASTMD 4052	0.879

The characteristic values appeared on the top in the table are typical values given only as an indication

Health and safety:

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of this product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.